



TOLERANCES UNLESS OTHERWISE SPECIFIED		ROUGHNESS		EXTERNAL FORM		SIZE		MATERIAL		REMARKS	
Ø130mm6	+0.030 +0.011 +0.040 +0.015	DIMENSION	TOL	SYMBOLS	PRIME	NO.	DESCRIPTIONS	DRAWN	DESIGNED	CHECKED	APPROVED
Ø75mm6	+0.030 +0.011 +0.040 +0.015	OVERHANGER	±0.1	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H		
16° 68°	±0.2	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
88° 125°	±0.4	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
125° 250°	±0.5	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
250° 500°	±0.6	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
500° 1000°	±0.8	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
1000° 2000°	±1.0	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
2000° 4000°	±1.5	▽▽▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				
ANGLE	±0.5	▽	0.08	55KW 6P 1/21-1/30	DATE	2010.12.21	J.R.H				

JEL ENGINEERING & INDUSTRIAL CO., LTD.