



() 안의 치수는 다소 변경 될 수 있음.

TOLERANCES UNLESS OTHERWISE SPECIFIED		ROUGHNESS		EXTERNAL FORM		SIZE		MATERIAL		REMARKS	
NO.	DESCRIPTIONS	NO.	DESCRIPTIONS	NO.	DESCRIPTIONS	NO.	DESCRIPTIONS	NO.	DESCRIPTIONS	NO.	DESCRIPTIONS
Ø90m6	+0.035	Ø90m6	+0.013	Ø90m6	+0.013	Ø90m6	+0.013	Ø90m6	+0.013	Ø90m6	+0.013
DIMENSION		TOL.		SYMBOLS		PART NAME		DATE		J.R.H	
OVERHUNG		±0.1		0.08		30KW 6P 1/5-1/20		2008.05.30		J.R.H	
16° 68°		±0.2		0.08		JK-VT 2200 REDUCER		40H6P20-V2200			
68° 125°		±0.4		0.08		DATE		2008.05.30			
125° 250°		±0.6		0.08		DWG.NO.		40H6P20-V2200			
250° 500°		±0.8		0.08		REL.NO.					
500° 1000°		±1.0		0.08							
1000° 2000°		±1.5		0.08							
2000° 4000°		±1.5		0.08							
ANGLE		±0.5		0.08							