



() 안의 치수는 다소 변경 될 수 있음.

| TOLERANCES UNLESS OTHERWISE SPECIFIED | | ROUGHNESS | | EXTERNAL FORM | | SIZE | | MATERIAL | | REMARKS | |
|---------------------------------------|--------|-------------|------|---------------|--------|--------------------|--------------|----------|----------|---------|----------|
| Ø90m6 | +0.035 | DIMENSION | TOL. | SYMBOLS | PRIMER | NO. | DESCRIPTIONS | DRAWN | DESIGNED | CHECKED | APPROVED |
| | | OVERHUNG | ±0.1 | ▽▽▽ | 0.01 | 15KW 8P 1/21~1/30 | | | | | |
| | | 4° 16° | ±0.2 | ▽▽▽ | 0.08 | JK-VT 2175 REDUCER | | | | | |
| | | 16° 68° | ±0.3 | ▽▽▽ | 0.38 | DWG.NO. | | | | | |
| | | 68° 125° | ±0.4 | ▽▽▽ | 6.38 | DATE | | | | | |
| | | 125° 250° | ±0.5 | ▽▽▽ | | 2007.09.20 | | | | | |
| | | 250° 500° | ±0.6 | ▽▽▽ | | 20H6P30-V2175 | | | | | |
| | | 500° 1000° | ±0.8 | ▽▽▽ | | | | | | | |
| | | 1000° 2000° | ±1.0 | ▽▽▽ | | | | | | | |
| | | 2000° 4000° | ±1.5 | ▽▽▽ | | | | | | | |
| | | ANGLE | ±0.5 | ▽ | 508 | | | | | | |