



( ) 안의 치수는 다소 변경 될 수 있음.

TOLERANCES UNLESS OTHERWISE SPECIFIED		ROUGHNESS		EXTERNAL FORM		NO.		DESCRIPTIONS		SIZE		MATERIAL		REMARKS	
Ø125m6	+0.015	0.040	0.015	0.040	0.015	0.040	0.015	0.040	0.015	0.040	0.015	0.040	0.015	0.040	0.015
DIMENSION		TOL.		SYMBOLS		Roughness		PART NAME		DATE		DWG. NO.		REL. NO.	
OVERHUNG		±0.1		▽▽▽		0.08		22KW 6P 1/31~1/60		2008.08.19		30H6P60-V3210			
4" 16"		±0.2		▽▽▽		0.08		JK-VT 3210 REDUCER							
16" 68"		±0.3		▽▽▽		0.08		SCALE		1 / 1					
68" 125"		±0.4		▽▽▽		0.08		PROJEC							
125" 250"		±0.5		▽▽▽		0.08		TION							
250" 500"		±0.6		▽▽▽		0.08									
500" 1000"		±0.8		▽▽▽		0.08									
1000" 2000"		±1.0		▽▽▽		0.08									
2000" 4000"		±1.5		▽▽▽		0.08									
ANGLE		±0.5		▽		508									